

# MATERIAL SAFETY DATA SHEET



## 1. Chemical Product and Company Identification

**Product Name: RACEPRO SC LOW DETERGENT OILS 30,40,50 WT MOTOR OILS**

**Chemical Name: Motor Oil**

**Chemical Family: Blend**

**Manufacturer: RACE PRO PRODUCTS  
RIVERSIDE, CA 92509**

**Emergency Telephone Number  
1-800-657-4811**

[www.raceprooil.com](http://www.raceprooil.com)

## 2. COMPOSITION INFORMATION ON INGREDIENTS

EXPOSURE GUIDELINES Component/CAS Number	OSHA		ACGIH		UNIT
	LO%	HI%	TWA	STEL	
LIMITS FOR THE PRODUCT			5	5	MG/M3
SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL 64741-88-4	.00	90.00	5	5	MG/M3
SEVERELY SOLVENT REFINED RESIDUUM 64742-01-4	.00	20.00	5	5	MG/M3

ADDITIONAL EXPOSURE LIMITS \_\_\_\_\_ GOVERNMENT REGULATION  
OTHER LIMIT - OIL MIST: 5MG/M3 OSHA PEL/ACGIH TLV

## 3. HAZARD IDENTIFICATION

### EMERGENCY OVERVIEW

MAY CAUSE SKIN IRRITATION

APPEARANCE: AMBER FLUID

ODOR: MOTOR OIL ODOR

POTENTIAL HEALTH EFFECTS:

INHALATION: NO EFFECTS EXPECTED.

INGESTION: PRACTICALLY NON-TOXIC.

EYE CONTACT: EXPECTED TO BE MINOR EYE IRRITANT.

SKIN CONTACT: PRACTICALLY NON-TOXIC IF ABSORBED (LD50 > 2000 MG/KG). MAY CAUSE

MODERATE IRRITATION WITH PROLONGED OR REPEATED CONTACT.

CARCINOGEN LISTED BY: IARC(NO) NTP(NO) OSHA(NO) ACGIH(NO) OTHER(NO)

### NTP/NIOSH CLASSIFICATION

HEALTH - 00

FLAMMABILITY - 1/1

REACTIVITY - 00

### HAZARD RATING

0-LEAST 1-SLIGHT

2-MODERATE 3-HIGH

4-EXTREME

NA=Not Applicable

ND=No Data

NE=Not Established

---

#### 4. FIRST AID MEASURES

---

**INHALATION:** Move to fresh air.

**EYE CONTACT:** Flush with water for at least 15 minutes. If irritation persists, obtain medical assistance.

**SKIN CONTACT:** Wash with soap and water until no odor remains. If redness or swelling develops, obtain medical assistance. Wash clothing before reuse.

**INGESTION:** Practically non-toxic. Induction of vomiting not required. Obtain emergency medical attention. Small amounts which accidentally enter mouth should be rinsed out until taste of it is gone.

---

#### 5. FIRE FIGHTING MEASURES

---

**FLASHPOINT (METHOD):** 428°F Minimum COC; 220°C Minimum COC

**FLAMMABLE LIMITS:** Not established

**AUTOIGNITION TEMP:** 675°F Estimated; 359°C Estimated

**EXTINGUISHING MEDIA:** Water spray, dry chemical, carbon dioxide (CO<sub>2</sub>), foam.

**FIRE FIGHTING INSTRUCTIONS:** Avoid breathing smoke and vapor.

**FIRE FIGHTING EQUIPMENT:** Wear self-contained breathing apparatus and protective clothing. Use water spray to keep fire-exposed containers cool.

**HAZARDOUS COMBUSTION PRODUCTS:** Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

---

#### 6. ACCIDENTAL RELEASE MEASURES

---

**SPILLS OR LEAKS:** Contain spill, advise EPA; state agency if required. Absorb on inert material, shovel, sweep or vacuum spill.

---

#### 7. HANDLING AND STORAGE

---

NFPA Class IIB Storage. Wash thoroughly after handling.

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**VENTILATION:** Ventilate as needed to comply with exposure limit. General dilution ventilation acceptable.

##### PERSONAL PROTECTIVE EQUIPMENT

**EYE:** Splash proof chemical goggles recommended to protect against splash of product.

**GLOVES:** Protective gloves recommended when prolonged skin contact cannot be avoided. The following glove materials are acceptable: polyvinyl chloride (PVC); neoprene; nitrile; polyvinyl alcohol; viton.

**RESPIRATOR:** Concentration in air determines protection needed. Use only NIOSH certified respiratory protection. Respiratory protection usually not needed unless product is heated or misted. Half-mask air purifying respirator with dust/mist filters or HEPA filter cartridges is acceptable to 10 times the exposure limit. Full face air purifying respirator with dust/mist filters or HEPA filter cartridges is acceptable to 50 times the exposure limit. Protection by air purifying respirators is limited. Use a positive pressure demand full face supplied air respirator or SCBA for exposures above 50X the exposure limit. If exposure is above IDLH (immediately dangerous to life and health) or there is the possibility of an uncontrolled release or exposure levels are unknown then use a positive pressure demand full face supplied air respirator with escape bottle or SCBA.

**OTHER:** If contact is unavoidable, wear chemical resistant clothing. The following materials are acceptable as protective clothing materials: polyvinyl alcohol (PVA); polyvinyl chloride (PVC); neoprene; nitrile; viton; polyurethane; launder soiled clothes.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>APPEARANCE/ODOR :</b> AMBER FLUID/MOTOR OIL ODOR.	<b>BOILING POINT:</b> HIGH
<b>VAPOR PRESSURE :</b> <0.0001 (MM HG @ 20°C)	<b>MELTING POINT:</b> N/A
<b>MOLECULAR WEIGHT:</b> N/A (G/MOLE)	<b>PACKING DENSITY:</b> N/A
<b>SOLUBILITY IN WATER:</b> NIL (% BY VOLUME)	<b>OCTANOL/WATER COEFF.:</b> N.D.
<b>EVAPORATION RATE:</b> 1000X SLOWER (ETHYL ETHER=1)	<b>ODOR THRESHOLD:</b> N.D.
<b>SPECIFIC GRAVITY:</b> 0.86 (WATER=1)	<b>VAPOR DENSITY:</b> 10+ (AIR =1)
<b>VISCOSITY:</b> 66.0 SUS @ 210°F	93.8 CST @ 40°C

---

### 10. STABILITY AND REACTIVITY

---

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** None known.

**MATERIALS TO AVOID:** Strong oxidizing agents.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION:** Combustion will produce carbon monoxide and asphyxiants.

---

### 11. TOXICOLOGICAL INFORMATION

---

**ORAL TOXICITY (RATS):** Practically non-toxic (LD50: greater than 2000 mg/kg).

**DERMAL TOXICITY (RABBITS):** Practically non-toxic (LD50: greater than 2000 mg/kg).

**INHALATION TOXICITY (RATS):** Practically non-toxic (LC50: greater than 5 mg/l).

**EYE IRRITATION (RABBITS):** Practically non-irritating. (Draize score: greater than 6 but 15 or less).

**SKIN IRRITATION (RABBITS):** Practically non-irritating. (Primary Irritation Index: greater than 0.5 but less than 3.)

**CHRONIC TOXICOLOGY:** The base oils in this product are severely solvent refined and / or hydrotreated. Chronic mouse skin painting studies of severely treated oils showed no evidence of carcinogenic effects. These results are confirmed on a continuing basis using various screening methods such as Modified Ames Test and IP-346.

---

### 12. ECOLOGICAL INFORMATION

---

**ECOTOXICITY:** No data available.

---

### 13. DISPOSAL INFORMATION

---

Follow federal, state and local regulations. Not RCRA hazardous waste if uncontaminated. If "used", RCRA criteria (ignitability, reactivity, corrosivity, toxicity characteristics) must be determined. Do not flush to drain/storm sewer. Contract to authorized disposal service.

---

### 14. TRANSPORTATION INFORMATION

---

**DOT**

<b>PROPER SHIPPING NAME</b>	Petroleum Lubricating Oil
<b>HAZARD CLASS:</b>	Not regulated
<b>ID NUMBER:</b>	Not regulated
<b>LABEL REQUIRED:</b>	Not-regulated
<b>IMDG PROPER SHIPPING NAME:</b>	N.D.

Page: 4 of 4

---

**15. REGULATORY INFORMATION**


---

TSCA: This material is in compliance with the TOXIC SUBSTANCES CONTROL ACT (15 USC 2601-2629) and is listed in the TSCA Inventory.

SARA 302 THRESHOLD PLANNING QUANTITY,	N/A		
SARA 304 REPORTABLE QUANTITY	N/A		
SARA 311/312 REPORTING:	Health	Immediate (Acute)	No
	Health	Delayed (Chronic)	No
	Physical	Fire	No
	Physical	Sudden Release of Pressure	No
	Physical	Reactive	No

When a product and/or component is listed below, the regulatory list on which it appears is indicated.

01=SARA 313	02= SARA 302/304	03=IARC CARCINOGEN
04=OSHA CARCINOGEN	05=ACGIH CARCINOGEN	06=NTP CARCINOGEN
07=CERCLA 302.4	08=WHMIS CONTROLLED PROD.	
10=OTHER CARCINOGEN		
PA=PA RTK	NJ=NEW JERSEY RTK	CA=CALIFORNIA PROP 65
MA=MASS. RTK	MI=MICHIGAN 406	MN=MINNESOTA RTK
FL=FLORIDA	RI=RHODE ISLAND	IL=ILLINOIS
NY=NEW YORK	WV=WEST VIRGINIA	CT=CONNECTICUT
LA=LOUISIANA	ME=MAINE	OH=OHIO

---

**16. OTHER INFORMATION**


---

**Caution!** Prolonged or repeated contact with used motor oil may be harmful to skin and could cause skin cancer. Promptly wash affected area with soap and water. WHMIS Classification: Not Controlled

**Manufacturer: RACE PRO PRODUCTS**  
**RIVERSIDE, CA 92509**  
[www.raceprooil.com](http://www.raceprooil.com)

**Emergency Telephone Number**  
**1-800-657-4311**

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of these data or the results to be obtained from the use thereof.

---

NA=Not Applicable    ND=No Data    NE=Not Established