

MATERIAL SAFETY DATA SHEET



1. Chemical Product and Company Identification

Product Name: RACEPRO ATF TYPE A

Chemical Name: TRANSMISSION FLUID

Chemical Family: Blend

Manufacturer: RACE PRO PRODUCTS

RIVERSIDE, CA 92509

www.raceproof.com

Emergency Telephone Number
1-800-657-4811

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT	WT.%	C.A.S. No.	TLV/ACGIH OSHA--)
Petroleum Distillates, Hydroreated Light Naphthenic	Blend	64742-63-6	5 mg/m3 (Msd)
Petroleum Distillates, Hydroreated Heavy Naphthenic	Blend	64742-62-6	5 mg/m3 (Msd)

Comments: The maximum percentage of the petroleum distillate and/or residual oil blend contained in the product is: 100%.
 All mineral oils used in this product have been severely hydroreated and/or solvent refined. Exact composition of the product will vary with availability of materials. All ingredients listed above may not be always included in final product. This product is considered not hazardous according to 29 CFR 1910.1200 (Hazard Communication).

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Specific Gravity (H ₂ O=1)	0.81	Appearance and Odor	Red liquid with petroleum odor
Solubility in Water	Negligible	pH	N/A
Flash Point (CO ₂), °F (°C)	340 (171)	Solubility in Solvent	Hydrocarbons
Flash Point, °F	N/A	%Volatiles By Wt	N/A
Vapor Pressure (mmHg)	N/A	Pour Point, °F (°C)	-15 (-25)
Evaporation Rate (Butyl Acetate=1)	N/A	Vapor Density (Air=1)	Heavier than air

SECTION IV FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA:	Water	xx	Foam	xx	CO ₂	xx	Dry	xx
SPECIAL FIRE FIGHTING PROCEDURES:	Wear self-contained, positive pressure breathing apparatus and impervious protective clothing. Avoid inhaling any combustion products.							
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Water steam may spread fire. Direct water spray or foam may cause roiling and spattering. Use water to cool fire-exposed containers and to protect personnel. If a leak or spill has not ignited, use water spray to disperse vapors and to flush spills away from exposure.							

SECTION V REACTIVITY DATA

Stable	xx	Unstable	Corrosive	No	Hazardous	Yes	No	xx
Polymersization?								
Incompatibilities: Strong oxidizing agents (peroxides, chlorates, strong acids).								
Hazardous Decomposition or Byproducts: Decomposition and combustion products may include fumes, smoke, sulfur dioxide, oxides of zinc, boron, magnesium, calcium, phosphorus, carbon monoxide, carbon dioxide and other low molecular weight hydrocarbons.								

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. While RacePro Products Company Inc. believes this data is accurate as of revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for your information, investigation, and ventilation.

SECTION VI HEALTH HAZARD INFORMATION	
Recommended TLV of Product	N/A
EYE	May cause irritation.
CONTACT	
INHA-	An unlikely way of exposure at standard temperatures and pressures. Inhalation of oil mists or fumes can cause irritation of the nose, throat and upper respiratory tract. Repeated and prolonged overexposure to oil mist may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection.
OTHER	None known.
SECTION VII EMERGENCY AND FIRST AID PROCEDURES	
EYE CONTACT	Flush with large amount of water for 15 minutes. Get medical attention if eye irritation develops or persists.
SKIN CONTACT	Wash immediately with soap and water. Remove contaminated clothing and wash before re-use. Get medical attention if skin disorder develops.
INHALATION	Remove individual to fresh air. If the affected person is not breathing, apply artificial respiration. Get medical attention if symptoms persist.
INGESTION	DO NOT INDUCE VOMITING. Get medical attention or advice.
SECTION VIII SPECIAL PROTECTION INFORMATION	
RESPIRATORY PROTECTION	Use with adequate ventilation.
RESPIRATORY PROTECTION	If mist is generated (heating, spraying) and engineering control are not sufficient, wear approved organic vapor respirator suitable for oil mist.
VENTILATION	Use with adequate ventilation.
EYE PROTECTION	Goggles or full-face shield.
PROTECTIVE CLOTHING	Neoprene gloves and apron.
SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE	
SPILL OR LEAK PROCEDURE	Observe health hazards described above, ventilate area. Remove ignition sources. Absorb with inert absorbent such as clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums.
WASTE DISPOSAL METHOD	Dispose in accordance with all local, state and federal regulations. Keep this product out of sewers and waterways.
STORAGE AND HANDLING PRECAUTIONS	Do not store this material in open or unlabeled containers. Do not store near heat sources, open flame or strong oxidizing agents. Empty containers retain product residue and can be dangerous. Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other source of ignition; they may explode.
OTHER PRECAUTIONS	Wearing contact lenses is inadvisable. Keep away from children and animals.